

ChangeMan[®] ZMF 8.1.4

Java / zFS Getting Started Guide

Proprietary and Confidential Information

Copyright © 2010-2017 Serena Software, Inc., a Micro Focus Company. All rights reserved.

This document, as well as the software described in it, is furnished under license and may be used or copied only in accordance with the terms of such license. Except as permitted by such license, no part of this publication may be reproduced, photocopied, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, recording, or otherwise, without the prior written permission of Serena. Any reproduction of such software product user documentation, regardless of whether the documentation is reproduced in whole or in part, must be accompanied by this copyright statement in its entirety, without modification.

This document contains proprietary and confidential information, and no reproduction or dissemination of any information contained herein is allowed without the express permission of Serena Software.

The content of this document is furnished for informational use only, is subject to change without notice, and should not be construed as a commitment by Serena. Serena assumes no responsibility or liability for any errors or inaccuracies that may appear in this document.

Trademarks

Serena, TeamTrack, StarTool, PVCS, Comparex, Dimensions, Prototype Composer, Mariner and ChangeMan are registered trademarks of Serena Software, Inc. The Serena logo, Version Manager and Mover are trademarks of Serena Software, Inc. All other products or company names are used for identification purposes only, and may be trademarks of their respective owners.

U.S. Government Rights

Any Software product acquired by Licensee under this Agreement for or on behalf of the U.S. Government, its agencies and instrumentalities is "commercial software" as defined by the FAR. Use, duplication, and disclosure by the U.S. Government is subject to the restrictions set forth in the license under which the Software was acquired. The manufacturer is Serena Software, Inc., 2345 NW Amberbrook Drive, Suite 200, Hillsboro, OR 97006 USA

Publication date: September 2017

Table of Contents

	Welcome to ChangeMan ZMF	5
	Guide to ChangeMan ZMF Documentation	5
	ChangeMan ZMF Documentation Suite	5
	Using the Manuals	7
	Searching the ChangeMan ZMF Documentation Suite	7
	Using Online Help	8
	Online Tutorial	8
	Online Help Screens	8
	Online Error Messages	8
	Typographical Conventions	9
<i>Chapter 1</i>	Introduction	11
	Java Support	12
	zFS in UNIX System Services under z/OS	12
	User Interface	12
	zFS Limitations	13
	No zFS In Converted Packages	13
	Functions Without zFS Support	13
<i>Chapter 2</i>	Working With zFS In ZMF	15
	Working with Long Fields in ISPF	16
	Scrolling LEFT and RIGHT	16
	Long Field Zoom - EXPAND	17
	Clearing Long Names From Panel Input Fields	18
	Alternate Panel - LONG and XLONG	18
	Right Justified Long Names in ERO	20
	Case Sensitive Fields	20
	Data Set Type	21
	Mixed Case	21
	Component Names That Contain A Path	23
<i>Chapter 3</i>	Configuring ZMF for Java/zFS	27
	Configure USS for ZMF	28
	Set ZMF User-ID Security for USS File Systems	28
	Create Top-Level Directory for ZMF zFS Files	29
	Adjust Security on zFS Files Managed by ZMF	29
	Increase MAXPROCUSER or PROCUSERMAX	29
	Enable CMNEX026 for LSH Listing	30
	Configure ZMF Global and Application Administration	30
	Global Staging Library Model zFS Name	30
	Global zFS Temporary Folder	31
	Global Site zFS Production Staging Model DSNAME	32

Global and Application Library Types	33
Global and Application Language and Compile Procedures	34
Application Baseline Libraries	34
Application Production Libraries	36
Application Promotion Libraries	37
Deploy Java Applications To WebSphere	37

Chapter 4

Working With Java	39
Java Build Processing	40
Compile Java Source	40
Build Java Archive	40
Build Web Archive	43
Impact Analysis for Java	44
Package Audit for Java	44
Package Out-of-Sync Conditions for Java	44
Package Audit Report for Java Components	45
ERO Audit for Java	47
Release Audit Error Numbers for Java	48
ERO Audit Report for Java Components	49

Appendix A

Technical Notes	51
CMNHUTIL - zFS File Utility	52
CMNHUTIL Input	52
Output	52
Sample JCL	53
DD Statements	53
PARM Options	53
SYSIN Parameters	53
Return Codes and Error Messages	56
Reporting	57
CMNHUTIL Examples:	57

Welcome to ChangeMan ZMF

Serena® ChangeMan® ZMF is a comprehensive and fully integrated solution for Software Change Management systems in z/OS environments. It provides reliable and streamlined implementation of software changes from development into production. ChangeMan ZMF manages and automates the application life cycle, protects the integrity of the code migration process, and results in higher quality delivered code to any test environment and to the production environment.

Before You Begin	See the Readme for the latest updates and corrections for this manual.
Audience and scope	<p>This document is an addendum to the ChangeMan ZMF documentation set. It provides information that is necessary to use ZMF to manage application components stored in USS file systems, especially Java application components.</p> <p>This document is intended for ChangeMan ZMF installers, global administrators, application administrators, and security administrators. It is also intended for developers who use ChangeMan ZMF to manage changes to applications with components stored in USS file systems.</p>
Navigating this book	<p>This manual is organized as follows:</p> <ul style="list-style-type: none">■ Chapter 1 provides an introduction to USS file support in ChangeMan ZMF.■ Chapter 2 describes how to work with USS file directories and file names in the ISPF interface to ChangeMan ZMF.■ Chapter 3 lists the steps required to configure ChangeMan ZMF to manage Java components and other zFS files.■ Chapter 4 tells developers how to use ChangeMan ZMF to work with Java components and applications.
Change Bars	Change bars in the left margin identify substantive changes in this publication since the last published version.

Guide to ChangeMan ZMF Documentation

The following sections provide basic information about ChangeMan ZMF documentation.

ChangeMan ZMF Documentation Suite

The ChangeMan ZMF documentation set includes the following manuals in PDF format.

Manual	Description
<i>Administrator's Guide</i>	Describes ChangeMan ZMF features and functions with instructions for choosing options and configuring global and application administration parameters.
<i>ChangeMan ZMF Quick Reference</i>	Provides a summary of the commands you use to perform the major functions in the ChangeMan ZMF package life cycle.

Manual	Description
<i>Customization Guide</i>	Provides information about ChangeMan ZMF skeletons, exits, and utility programs that will help you to customize the base product to fit your needs.
<i>DB2 Option Getting Started Guide</i>	Describes how to install and use the DB2 Option of ChangeMan ZMF to manage changes to DB2 components.
<i>ERO Concepts</i>	Discusses the concepts of the ERO Option of ChangeMan ZMF for managing releases containing change packages.
<i>ERO Getting Started Guide</i>	Explains how to install and use the ERO Option of ChangeMan ZMF to manage releases containing change packages.
<i>ERO Messages</i>	Describes system messages and codes produced by ChangeMan ZMF ERO.
<i>ERO XML Services User's Guide</i>	Documents ERO functions and services available for general customer use. These services are also known as the "green" services and provide mostly search and query functions.
<i>High-Level Language Functional Exits Getting Started Guide</i>	Provides instructions for implementing and using High-Level Language (Cobol, PL/1, and REXX) exits, driven consistently by all clients to enforce local business rules in ZMF functions.
<i>IMS Option Getting Started Guide</i>	Provides instructions for implementing and using the IMS Option of ChangeMan ZMF to manage changes to IMS components.
<i>INFO Option Getting Started Guide</i>	Describes two methods by which ChangeMan ZMF can communicate with other applications: <ul style="list-style-type: none"> ■ Through a VSAM interface file. ■ Through the Tivoli Information Management for z/OS product from IBM.
<i>Installation Guide</i>	Provides step-by-step instructions for initial installation of ChangeMan ZMF. Assumes that no prior version is installed or that the installation will overlay the existing version.
<i>Java / zFS Getting Started Guide</i>	Provides information about using ZMF to manage application components stored in USS file systems, especially Java application components.
<i>Load Balancing Option Getting Started Guide</i>	Explains how to install and use the Load Balancing Option of ChangeMan ZMF to connect to a ChangeMan ZMF instance from another CPU or MVS image.
<i>M+R Getting Started Guide</i>	Explains how to install and use the M+R Option of ChangeMan ZMF to consolidate multiple versions of source code and other text components.
<i>M+R Quick Reference</i>	Provides a summary of M+R Option commands in a handy pamphlet format.
<i>Messages</i>	Explains messages issued by ChangeMan ZMF, SERNET, and System Software Manager (SSM) used for the Staging Versions feature of ChangeMan ZMF.

Manual	Description
<i>ChangeMan ZMF Migration Guide</i>	Gives guidance for upgrading ChangeMan ZMF.
<i>OFM Getting Started Guide</i>	Explains how to install and use the Online Forms Manager (OFM) option of ChangeMan ZMF.
<i>SER10TY User's Guide</i>	Gives instructions for applying licenses to enable ChangeMan ZMF and its selectable options.
<i>User's Guide</i>	Describes how to use ChangeMan ZMF features and functions to manage changes to application components.
<i>XML Services User's Guide</i>	Documents the most commonly used features of the XML Services application programming interface to ChangeMan ZMF.

Using the Manuals

Use Adobe® Reader® to view ChangeMan ZMF PDF files. Download the Reader for free at get.adobe.com/reader/.

This section highlights some of the main Reader features. For more detailed information, see the Adobe Reader online help system.

The PDF manuals include the following features:

- **Bookmarks.** All of the manuals contain predefined bookmarks that make it easy for you to quickly jump to a specific topic. By default, the bookmarks appear to the left of each online manual.
- **Links.** Cross-reference links within a manual enable you to jump to other sections within the manual with a single mouse click. These links appear in blue.
- **Comments.** All PDF documentation files that Serena delivers with ChangeMan ZMF have enabled commenting with Adobe Reader. Adobe Reader version 7 and higher has commenting features that enable you to post comments to and modify the contents of PDF documents. You access these features through the Comments item on the menu bar of the Adobe Reader.
- **Printing.** While viewing a manual, you can print the current page, a range of pages, or the entire manual.
- **Advanced search.** Starting with version 6, Adobe Reader includes an advanced search feature that enables you to search across multiple PDF files in a specified directory.

Searching the ChangeMan ZMF Documentation Suite

There is no cross-book index for the ChangeMan ZMF documentation suite. You can use the Advanced Search facility in Adobe Acrobat Reader to search the entire ZMF book set for information that you want. The following steps require Adobe Reader 6 or higher.

- 1 Download the ZMF All Documents Bundle ZIP file and the ZMF Readme to your workstation from the My Downloads tab on the Serena Support website.

-
- 2 Unzip the PDF files in the ZMF All Documents Bundle into an empty folder. Add the ZMF Readme to the folder.
 - 3 In Adobe Reader, select **Edit | Advanced Search** (or press **Shift+Ctrl+F**).
 - 4 Select the **All PDF Documents in** option and use **Browse for Location** in the drop down menu to select the folder containing the ZMF documentation suite.
 - 5 In the text box, enter the word or phrase that you want to find.
 - 6 Optionally, select one or more of the additional search options, such as **Whole words only** and **Case-Sensitive**.
 - 7 Click **Search**.
 - 8 In the **Results**, expand a listed document to see all occurrences of the search argument in that PDF.
 - 9 Click on any listed occurrence to open the PDF document to the found word or phrase.

Using Online Help

Online help is the primary source of information about ChangeMan ZMF. Online help is available as a tutorial, through Help screens, and in ISPF error messages.

Online Tutorial

ChangeMan ZMF includes an online tutorial that provides information about features and operations, from high-level descriptions of concepts to detailed descriptions of screen fields.

To view the tutorial table of contents, select option T from the Primary Option Menu, or jump to it from anywhere in ChangeMan ZMF by typing =T and pressing ENTER.

Press PF1 from anywhere in the Tutorial for a complete list of Tutorial navigation commands and PF keys.

Online Help Screens

If you have questions about how a ChangeMan ZMF screen works, you can view a help panel by pressing PF1 from anywhere on the screen.

Online Error Messages

If you make an invalid entry on a ChangeMan ZMF screen, or if you make an invalid request for a function, a short error message is displayed in the upper right corner of the screen. Press PF1 to display a longer error message that provides details about the error condition.

Remember that the long message does not display automatically. Request the long message by pressing PF1.

Typographical Conventions

The following typographical conventions are used in the online manuals and online help. These typographical conventions are used to assist you when using the documentation; they are not meant to contradict or change any standard use of typographical conventions in the various product components or the host operating system.

Convention	Explanation
<i>italics</i>	Introduces new terms that you may not be familiar with and occasionally indicates emphasis.
bold	Indicates panel titles, field names, and emphasizes important information.
UPPERCASE	Indicates keys or key combinations that you can use. For example, press ENTER.
monospace	Indicates syntax examples, values that you specify, or results that you receive.
<i>monospaced italics</i>	Indicates names that are placeholders for values you specify; for example, <i>filename</i> .
monospace bold	Indicates the results of an executed command.
vertical rule	Separates menus and their associated commands. For example, select File Copy means to select Copy from the File menu. Also, indicates mutually exclusive choices in a command syntax line.

Chapter 1

Introduction

Serena ChangeMan ZMF includes support for Java applications, providing:

- Secure, rules based management of Java application artifacts in ChangeMan package life cycle
- Stability, reliability, and security of the mainframe platform
- ZMF for Eclipse and RDz user interfaces.

Java Support	12
zFS in UNIX System Services under z/OS	12
User Interface	12
zFS Limitations	13

Java Support

Java application components that are managed by ChangeMan ZMF include:

- Java source
- Java class
- JAR build control
- JAR
- WAR build control
- WAR
- Java application HTML
- Other Java application artifacts

Java build processes in ChangeMan ZMF create the following:

- Java class
- JAR
- WAR

zFS in UNIX System Services under z/OS

Support for Java includes support for zFS files under UNIX System Services in z/OS. ChangeMan ZMF supports zFS files with names up to 255 characters and zFS path names up to 1023 characters long.

zFS directory paths and file are used for Java components in place of PDS(E) libraries for the following:

- Staging
- Promotion
- Production
- Baseline

User Interface

While the ISPF interface to ChangeMan ZMF is modified to accommodate the long zFS path and component names required for Java, most Java developers will be unfamiliar with the mainframe environment and will not be efficient working through the ISPF interface.

ChangeMan ZMF works with IDEs like Eclipse and RDz that provide a more familiar environment for Java developers. Ask your account representative about the ChangeMan ZMF Client Pack, which includes ChangeMan for Eclipse, an integration plug-in for both IBM Rational Developer and the open-source Eclipse IDE.

zFS Limitations

There are some limitations on the use of zFS in ChangeMan ZMF 8.1.

No zFS In Converted Packages

If you upgrade from a version before 7.1, you cannot check out or stage a zFS component into a package that was created before you upgraded.

The package records created in an earlier ZMF version do not contain the zFS staging model data set names that you enter in global administration after you convert the package master from an earlier version.

You can only check out or stage zFS components into packages created in ChangeMan ZMF 7.1 or later.

Functions Without zFS Support

These functions do not support zFS files in ChangeMan ZMF:

- Scan Baseline For Character Strings (=1.S) - short message 'NOT SUPPORTED' and Long message: 'CMN6503I - Scan of this baseline storage means is not supported.'
- Scan sub-function of Browse\Print\Copy Baseline Or Promotion (=1.B)
- M+R Option (=C)

Previously this was not available but now this function does support zFS files in ChangeMan ZMF:

- Compare Staging To Baseline Or Promotion (=1.C)

Chapter 2

Working With zFS In ZMF

Serena ChangeMan ZMF includes support for Java applications, providing:

- Secure, rules based management of Java application artifacts in ChangeMan package life cycle
- Stability, reliability, and security of the mainframe platform
- ZMF for Eclipse and RDz user interfaces.

Working with Long Fields in ISPF	16
Case Sensitive Fields	20
Component Names That Contain A Path	23

Working with Long Fields in ISPF

Component names in USS file systems can be 256 characters long, and path names can be 1024 characters long.

In the ChangeMan ZMF ISPF interface, there are three ways users can see a long component or path name on a panel whose total width is limited to 80 characters.

- Scroll in the panel field
- Zoom in on the field with EXPAND
- Display an alternate panel

In this section, example package ACTP000052 contains these components:

Staging Library (Path) Name	Component Name
/cmntp/s6/ACTP/#000052/d/JVS	hellow.java
/cmntp/s6/ACTP/#000052/d/JCT	hellow.jct
/cmntp/s6/ACTP/#000052/d/JVS	org/dom/xpath/jhfhth30long.java
/cmntp/s6/ACTP/#000052/d/HTH	org/jdom/xpath/jhfhth30long.hth
/cmntp/s6/ACTP/#000052/d/HTH	testfile.hth



IMPORTANT! In USS file systems, a "component name" may include a partial directory path because the actual name of the file is unique only within a hierarchy that includes it.

When line command **S2** is entered by package ACTP000052 on the **Change Package List** panel, the **Stage: package Components** panel (CMNSTG01) is displayed in this format.

CMNSTG01		STAGE: ACTP000052 Components					Row 1 to 5 of 5	
Command ==>							Scroll ==> CSR	
Name	+ Type	Status	Changed		Procname	User	Request	
___ hellow.java	JVS	ACTIVE	20150305 145828		CMNJAVA	USER015		
___ hellow.jct	JCT	ACTIVE	20150309 184115		CMNJAR	USER015		
___ org/dom/xpath/jhfh	JVS	ACTIVE	20150309 200446		CMNJAVA	USER015		
___ org/jdom/xpath/jhf	HTH	ACTIVE	20150309 192827			USER015		
___ testfile.hth	HTH	ACTIVE	20150309 192103			USER015		
***** Bottom of data *****								

When a data field is *longer* than the panel field used to display it, a + (plus) is shown to the right of the panel field. If the panel field is in a list, the + is shown over the panel field column, in the heading, as shown in the example above.

Notice that the names of the first two components and the last component fit in the **Name** column field. However, the names of the third and fourth components appear to overflow the Name field.

Scrolling LEFT and RIGHT

To see more of a long name that is truncated by a short panel field, you can scroll to the right, and then scroll back to the left.

- To scroll to the *right* in a field, place your cursor in the field and press **PF11**. (You can also type **RIGHT** in the **Command** line, place your cursor in the field, and press **ENTER**.)
- To scroll to the *left* in a field, place your cursor in the field and press **PF10**. (You can also type **LEFT** in the **Command** line, place your cursor in the field, and press **ENTER**.)

This panel shows the **Name** field after scrolling right one time.

CMNSTG01		STAGE: ACTP000052 Components				Row 1 to 5 of 5	
Command ==>						Scroll ==> CSR	
Name	-+ Type	Status	Changed	Procname	User	Request	
—	JVS	ACTIVE	20150305 145828	CMNJAVA	USER015		
—	JCT	ACTIVE	20150309 184115	CMNJAR	USER015		
— fhth30long.java	JVS	ACTIVE	20150309 200446	CMNJAVA	USER015		
— hfhth30long.hth	HTH	ACTIVE	20150309 192827		USER015		
—	HTH	ACTIVE	20150309 192103		USER015		
***** Bottom of data *****							

Rules for scrolling in long panel fields:

- The **SCROLL** amount at the upper right of the panel determines the scroll amount for long panel fields.
- You might have to scroll right more than once to see the end of a long field.
- When you have scrolled to right end of a long field, a - (minus) replaces the + (plus) to indicate that you can only scroll left from that point
- Both -+ (minus plus) are displayed when you can scroll both right and left from your current position in a long field.
- If you type **M** (MAXIMUM) on the **Command** line before you position your cursor in a long field, when you press **PF11** or **PF10** the field scrolls all the way to the end or the beginning respectively.

Long Field Zoom - EXPAND

Rather than pressing **PF11** or **PF10** multiple times to scroll through a long field, you can zoom in on the field by placing your cursor over the field and pressing **PF4** to execute the ISPF **EXPAND** command. EXPAND displays the entire field in a pop-up panel.

If you place the cursor on the **NAME** field of the fourth component listed on the STAGE: package COMPONENTS panel above and you press **PF4**, the pop-up **CMNAME+0** panel (ISPEXPND) is displayed.

+----- CMNAME+0 -----+	
ISPEXPND	Line 1 of 4
Command ==>	Scroll ==> PAGE
org/jdom/xpath/jhfhth30long.hth	
...	
+-----	+-----

Zoom panel rules:

- The pop-up panel has the same attributes as the original panel field. If the original panel field is display-only, then the pop-up panel is also display-only. If the original panel field is available for input, you can type on the pop-up panel.
- If the original panel field is available for input, you can type up to 256 characters on multiple pop-up panel lines for a component name, or 1024 characters on multiple lines for a path name.
- Press **PF3** to exit the pop-up long name panel and return to the original panel.



NOTE Most ZMF panels in the ISPF interface follow this rule: "Press ENTER to process; Enter END or CANCEL command to exit." However, the pop-up panel for expanded long name fields requires END or PF3 to save data entered or changed on the panel.

Clearing Long Names From Panel Input Fields

If a long name extends beyond the visible end of an input field on a ChangeMan ZMF panel, you must take care to:

- Clear the entire long name before pressing ENTER to display a selection list.
- Clear any parts of the old name that extend beyond a shorter name that you type over the original name.

If you only clear the visible part of a long name input field, the rest of the name remains in the ISPF variable, and it will interfere with the processing of subsequence input until you exit the panel. (This is an ISPF behavior, not a ZMF shortcoming.)



TIPS The quickest way to ensure that you have cleared a long name input field is to press PF4 to display the entire long name in a pop-up panel, erase all lines that contain parts of the long name, and press PF3 to return to the original panel.

Alternate Panel - LONG and XLONG

In many ChangeMan ZMF functions that display a list of components, you can invoke an alternate panel that displays the component name on a separate line so there is room to show more characters of a long component name.

For example, if you have zFS library types in a package, then the **STAGE: package Components** panel (CMNSTG01) is displayed to show the components in the package.

```
CMNSTG01                      STAGE: ACTP000057 Components                      Row 1 to 3 of 3
Command ===> _____ Scroll ===> CSR_

  Name          + Type Status  Changed      Procname User   Request
__ averylongnamegoesh JVS  ACTIVE   20150315 161850 CMNJAVA  USER015
__ hw001.java      JVS  ACTIVE   20150315 152357 CMNJAVA  USER015
__ org/jdom/xpath/jhf JVS  ACTIVE   20150315 165512 CMNJAVA  USER015
***** Bottom of data *****
```

This panel CMNSTG01 shows only 18 characters of each component name. The panel permits scrolling left and right via PF10 and PF 11, and Expand (PF4) in the Name field so you can see the rest of the component name.

However, if you type **LONG** on the **Command** line and press **ENTER**, a different **STAGE: package Components** panel (CMNSTG14) is displayed, which shows each component zFS path, up to 44 characters, on a line below the rest of the component information.

CMNSTG14		STAGE: ACTP000057 Components					Row 1 to 3 of 3	
Command ==>							Scroll ==> CSR	
Name		+ Type	Status	Changed		Procname	User	Request
		Org	Input dataset name					+ Target lib
___	averylongnamegoesh	JVS	ACTIVE	20150315 161850	CMNJAVA	USER015		
		zFS	/cmntp/s6/ACTP/#000057/d/JVS					JVL
___	hw001.java	JVS	ACTIVE	20150315 152357	CMNJAVA	USER015		
		zFS	/cmntp/s6/ACTP/#000057/d/JVS					JVL
___	org/jdom/xpath/jhf	JVS	ACTIVE	20150315 165512	CMNJAVA	USER015		
		zFS	/cmntp/s6/ACTP/#000057/d/JVS					JVL
***** Bottom of data *****								

This panel still only shows up to 18 characters of a long component name. This panel also offers scrolling and zoom in the Name field if you still cannot see the entire component name.

To return to the original component list panel, type **SHORT** on the **Command** line and press **ENTER**.

Prior to the release of ChangeMan ZMF 7.1 with long names, some panels already responded to the **LONG** command by displaying a panel with additional information. In some of these cases, you can type **XLONG** in the **Command** line and press **ENTER** to display a special panel for long names.

If you type **XLONG** on the **Command** line and press **ENTER**, a further **STAGE: package Components** panel (CMNSTG24) is displayed. This panel shows each component name on a line above the component information, with the staging directory path on a third line.

CMNSTG24		STAGE: ACTP000057 Components					Row 1 to 3 of 3	
Command ==>							Scroll ==> CSR	
Name		+ Type	Status	Changed	Procname	User	Request	
		Org	Input dataset name				+ Target lib	
___ averylongnamegoeshereforjava.java		JVS	ACTIVE	20150315 161850	CMNJAVA	USER015		
		zFS	/cmntp/s6/ACTP/#000057/d/JVS				JVL	
___ hw001.java		JVS	ACTIVE	20150315 152357	CMNJAVA	USER015		
		zFS	/cmntp/s6/ACTP/#000057/d/JVS				JVL	
___ org/jdom/xpath/jhfhth40long.java		JVS	ACTIVE	20150315 165512	CMNJAVA	USER015		
		zFS	/cmntp/s6/ACTP/#000057/d/JVS				JVL	
***** Bottom of data *****								

This panel shows up to 75 characters of a long component name. This panel also offers scrolling and zoom in the **Name** field if you still cannot see the entire component name. You can scroll and zoom on the staging directory path.

On this panel you can use the **LONG** command to display the CMNSTG14 panel or **SHORT** to display the CMNSTG01 panel.



TIP If you want to see the component name on a separate line, try **XLONG** first. If short message INVALID SELECTION CODE is displayed, try command **LONG**.

Right Justified Long Names in ERO

ERO uses dynamic ISPF panels to make lists of components for functions like checkin, retrieve, query component, test area, test release, and promotion. ISPF does not support scroll RIGHT and LEFT on dynamic panels.

To display as much meaningful information in the long name column as possible where scroll is not supported, ERO right justifies long names on dynamic panels, truncating any extension on the file name.

In this example, release package JZFS00023 contains the following files with names that include a partial path:

```
/org/jdom/adapters/package.html
/org/jdom/filter/package.html
/org/jdom/input/package.html
/org/jdom/output/package.html
/org/jdom/package.html
/org/jdom/transform/package.html
```

See how these component names are displayed on ERO panel CMNCKI02, right justified with the extension *html* stripped off.

```
CMNCKI02  RELEASE CHECKIN JZFS00023 COMPONENTS ----- Row 000001 of 000006
COMMAND ==>
      COMPONENT NAME      TYPE  STATUS      CHANGED      PROCNAME      ID      AREA ID
Line Command: S-Select          ( SETALL Select all, SETOFF De-select all )
_ adapters/package      HTH   ACTIVE    20101124 141227      USER240      ACCTPAY
_ m/filter/package      HTH   ACTIVE    20101124 141231      USER240      ACCTPAY
_ om/input/package      HTH   ACTIVE    20101124 141232      USER240      ACCTPAY
_ m/output/package      HTH   ACTIVE    20101124 141234      USER240      ACCTPAY
_ org/jdom/package      HTH   ACTIVE    20101124 141235      USER240      ACCTPAY
_ ransform/package      HTH   ACTIVE    20101124 141237      USER240      ACCTPAY
***** Bottom of Data *****
```



NOTE Long names on ERO dynamic panels may be displayed using the PF4 zoom function to display the entire name in a pop-up window.

Case Sensitive Fields

By default, all ISPF panel input fields are folded to upper case, regardless of the case you type. However, zFS path names and file names are case sensitive. For example, these are three different files:

- FirstJavaComponent.java
- firstjavacomponent.java
- FIRSTJAVACOMPONENT.java

ChangeMan ZMF uses two methods to control the case sensitivity of input fields on ISPF panels.

- **Data Set Type** in library type definitions
- **Mixed Case** parameter on component list

Data Set Type

The global and application **Library Types Part 2 of 2** panel includes the **Data Set Type** field, with valid values of **LIBRARY** for PDSE, **PDS** or blank for PDS or **zFS**. When you type a component name or directory path for a data set type zFS, case is preserved and stored in ZMF repositories. When component name or directory path are displayed for data set type zFS, the case that is stored in ZMF repositories is displayed unchanged on ISPF panels.

For example, when you type information on the **application/site - Promotion Libraries** panel in application administration, ChangeMan ZMF uses the library type to determine whether the data should default to upper case or be processed exactly as you enter it.

In this example, the library names and directory paths for promotion are all entered in lower case (panel shows one JCL and one zFS libraries - JCL is uppercase).

CMNLRPM3		ACTP/SERT6 - Promotion Libraries		Row 2 to 8 of 8	
Command ==>				Scroll ==> CSR	
Promotion name: S6P1UT Level: 10					
Syslib					
Lib exclude	Target libraries				
_____ JCL Y	CMNTP.S6.V810.PROM.S6P1UT.JCL	+ Shadow			
	CMNTP.S6.V810.PROM.S6P1UT.JCL	+ Library 1			
		+ Library 2			
		+ Library 3			
_____ JVS N	/cmntp/s6/actp/prom10/jvs	+ Shadow			
	/cmntp/s6/actp/prom10/jvs	+ Library 1			
		+ Library 2			
		+ Library 3			
...					

When you press **ENTER**, the data set names for library type JCL are changed to upper case and stored that way on the package master. However, the zFS path names for library type JVS (Java) are left exactly as you entered them, and they are stored in mixed case on the package master.

Mixed Case

On list parameter panels where you specify filter criteria for building a component list, you can control how case is used in component name selection by setting the Mixed Case field.

/ Mixed case

By default, the text you enter in a component name field is folded to upper case before it is matched against component names. However, if you select the **Mixed Case** field, then the value you enter is compared exactly to the component name in whatever file or directory is being searched.

For example, package ACTP000054 contains these two components:

```
CMNSTG01          STAGE: ACTP000050 Components          Row 1 to 2 of 2
Command ==>                               Scroll ==> CSR

  Name          + Type Status   Changed          Procname User    Request
  acpdoc60      HTH  ACTIVE    20150315 212025      USER015
  ACPDOC60      DOC  ACTIVE    20150315 211855      USER015
***** Bottom of data *****
```

You can filter the components displayed on the **Stage: package Components** panel by first setting selection criteria on the **Component List Parameters** panel (CMNSTG12). If you type the **Component Name** field in lower case on the **Component List Parameters** panel and select the **Mixed case** field, then the filter is case sensitive, and only the HTH component is listed.

Selection criteria:

```
CMNSTG12          Component List Parameters
Command ==> _____

      Package: ACTP000050      Status: DEV      Install date: 20150318

Component name . . . . . acpdoc60      +
Component type . . . . . _____
Language . . . . . _____
Component status . . . . . _ (1-active, 2-incomplete,
                               3-checkout, 4-inactive)
Changed date: from . . . . . _____ (yyyymmdd)
                  to . . . . . _____ (yyyymmdd)
Compile procedure . . . . . _____
User . . . . . _____
Display mode . . . . . S (S-short, L-long, X-extra long)

Enter "/" to select option
  / Confirm component delete      / Confirm other requests
  _ Display component user options / Mixed case
  / Comparison report for edit    Text type . . . $._____
  _ Ignore recompiled components
```

Result:

```
CMNSTG01          STAGE: ACTP000050 Components          Row 1 to 1 of 1
Command ==>                               Scroll ==> CSR

  Name          + Type Status   Changed          Procname User    Request
  _ acpdoc60      HTH  ACTIVE    20150315 212025      USER015
***** Bottom of data *****
```

If you type the **Component Name** field in lower case and do not select the **Mixed Case** field, then the component name you typed is folded to upper case, and only the DOC component is listed.

Selection criteria:

```

CMNSTG12                                Component List Parameters
Command ==> _____

          Package: ACTP000050      Status: DEV      Install date: 20150318

Component name . . . . . acpdoc60      +
Component type . . . . . _____
Language . . . . . _____
Component status . . . . . -           (1-active, 2-incomplete,
                                         3-checkout, 4-inactive)
Changed date: from . . . . . _____ (yyyymmdd)
              to . . . . . _____ (yyyymmdd)
Compile procedure . . . . . _____
User . . . . . _____
Display mode . . . . . S              (S-short, L-long, X-extra long)

Enter "/" to select option
  / Confirm component delete           / Confirm other requests
  _ Display component user options     / Mixed case
  / Comparison report for edit        Text type . . . . $._____
  _ Ignore recompiled components

```

Result:

```

CMNSTG01                                STAGE: ACTP000050 Components      Row 1 to 1 of 1
Command ==> _____      Scroll ==> CSR

   Name          + Type Status  Changed      Procname User      Request
  _ ACPDOC60      DOC  ACTIVE   20150315 211855      USER015
***** Bottom of data *****

```

Component Names That Contain A Path

In USS file systems, a "component name" may include a partial directory path because the actual name of the file is unique only within a hierarchy that includes it.

ChangeMan ZMF automatically handles component names that include a directory path. However, when you stage an zFS component from development, you must indicate whether you want to choose a file name from the specified directory or a path name and file name from that directory.

On the **Stage: From Development** panel, the **Expand** field controls what is displayed on a component selection list. When you set the **Expand** field to **Yes**, all files and paths below the subdirectory you specify in the **DSN** field are displayed on the component selection panel.

Here is the stage panel.

```

CMNSTG02                               Stage from Development
Command ==> _____

Package: ACTP000050      Status: DEV      Install date: 20150318

ISPF Library:
  Project . . . . . USER015
  Group . . . . . JAVA
  Type . . . . . SRC
  Member . . . . . _____ (Blank/pattern for list; * for all members)

Other partitioned, sequential or zFS dataset:
  DSN . . . . . /cmntp/s4/v710/base/jzfs/jav/lvl-0/ +
  Org . . . . . _____ (PDS, Seq, PAN, LIB, Oth, zFS)

Library type . . . . . JVS (Blank for list)
Stage name . . . . . _____ +
Stage mode . . . . . 1 (1-Online, 2-Batch)

Enter "/" to select option
  / Expand zFS subdirectories
  / Confirm request
  _ Lock component
  _ Display component user options

```

Here is the resulting component selection list.

CMNSTG23		Stage from zFS file				Row 1 to 6 of 6	
Command ==>						Scroll ==> CSR	
Input filename							
/cmntp/s4/v710/base/jzfs/jav/lvl-0/						+	
Name	+	Function	Created	Changed	Size	User	
jhfjav40.java			2010/07/20	2010/11/05 16:30	00126	SERT	
jhfjav50.java			2010/11/05	2010/11/05 16:49	00126	SERT	
jhfjav60.java			2010/11/05	2010/11/05 17:23	00126	SERT	
org/jdom/xpath/jhfj			2010/07/20	2010/07/01 18:53	00151	SERT	
org/jdom/xpath/jhfj			2010/07/20	2010/07/01 18:54	00155	SERT	
org/jdom/xpath/jhfj			2010/07/20	2010/07/01 18:54	00154	SERT	
***** Bottom of data *****							

Notice that after the first three files, three more components are listed that are in a path of subdirectories below the directory you specified on the **Stage: From Development** panel. If you select one of the files with path names to stage into your package, the component name in the package master and in the component master will include the subdirectories as well as the file name.

Here, **Expand** zFS subdirectories is **not** selected.

```

CMNSTG02                               Stage from Development
Command ==> _____

          Package: ACTP000050      Status: DEV      Install date: 20150318

ISPF Library:
  Project . . . . . USER015
  Group . . . . . JAVA
  Type . . . . . SRC
  Member . . . . . _____ (Blank/pattern for list; * for all members)

Other partitioned, sequential or zFS dataset:
  DSN . . . . . /cmntp/s4/v710/base/jzfs/jav/lvl-0/ +
  Org . . . . . _____ (PDS, Seq, PAN, LIB, Oth, zFS)

Library type . . . . . JVS (Blank for list)
Stage name . . . . . _____ +
Stage mode . . . . . 1 (1-Online, 2-Batch)

Enter "/" to select option
  _ Expand zFS subdirectories
  / Confirm request
  _ Lock component
  _ Display component user options

```

The resulting component selection panel displays only the three components that are contained as files in the directory you specified on the **Stage: From Development** panel.

```

CMNSTG23                               Stage from zFS file      Row 1 to 3 of 3
Command ==>                               Scroll ==> CSR

Input filename
/cmntp/s4/v710/base/jzfs/jav/lvl-0/      +

Name      +      Function Created      Changed      Size User
jhfjav40.java      2010/07/20  2010/11/05 16:30  00126 SERT
jhfjav50.java      2010/11/05  2010/11/05 16:49  00126 SERT
jhfjav60.java      2010/11/05  2010/11/05 17:23  00126 SERT
***** Bottom of data *****

```



NOTE On the Stage: From Development panel (CMNSTG02), you cannot provide a STAGE NAME when the EXPAND field is selected.

Chapter 3

Configuring ZMF for Java/zFS

This chapter provides instructions for setting up ChangeMan ZMF to manage Java components in zFS directories under Unix System Services.

Configure USS for ZMF	28
Enable CMNEX026 for LSH Listing	30
Configure ZMF Global and Application Administration	30
Deploy Java Applications To WebSphere	37

Configure USS for ZMF

Before you can start making global and application administration entries to support Java application components, you must configure Unix System Services and your security system so that the SERNET / ZMF started task can create a secure environment in an zFS file system in USS.

The instructions in this section describe commands for z/OS Security Server RACF. If you use CA ACF2 or CA Top Secret, consult with your security administrator to determine the corresponding actions that are required in those security systems to accomplish the same objectives.

In the commands that follow, these conventions are used:

- **SERUSER** is the user-id assigned to the SERNET / ZMF started task.
- **SERGRP** is the RACF group assigned to the SERNET / ZMF started task.
- **/serdir** is the high-level zFS directory created for user-id SERUSER.

Set ZMF User-ID Security for USS File Systems

Prior to Version 7.1, the ChangeMan ZMF Installation Guide directed you to create an OMVS segment with UID(0) for the userid assigned to the SERNET / ZMF started task. Starting with ZMF 7.1, SERNET and ChangeMan ZMF can perform all necessary USS functions with more restrictive privileges.

Adjust USS privileges for SERUSER, the user-id (owner) of SERNET / ZMF started tasks:

- 1 Assign a non-zero UID to SERUSER by manually assigning the next available value:

```
ALTERUSER SERUSER OMVS(UID(XXX))
```

- 2 Permit access for SERUSER to two resources so it can manage zFS in USS:

```
PERMIT BPX.SERVER CLASS(FACILITY) ID(SERUSER) ACCESS(UPDATE)
PERMIT SUPERUSER.FILESYS CLASS(UNIXPRIV) ID(SERUSER) ACCESS(READ)
SETROPTS RACLIST(FACILITY) REFRESH
SETROPTS RACLIST(UNIXPRIV) REFRESH
```

- 3 Ensure that the SERUSER default group SERGRP has a GID:

```
ALTERGROUP SERGRP OMVS(GID(YYY))
```



NOTES In early editions of this manual, instructions for setting up security for USS file systems included steps to activate profile FILE.GROUPOWNER.SETGID in the UNIXPRIV class to ensure that anything created by the started task user ID inherits the started task GID. The intention was to guarantee that the entire zFS directory/file structure has consistent owner/group assignments.

It has been determined that the default behavior for USS is to propagate group ownership downwards for all directories and files that ChangeMan ZMF creates under the top level ZMF directory. Therefore, profile FILE.GROUPOWNER.SETGID is not required, and instructions for enabling it are removed from later editions of this book.

Create Top-Level Directory for ZMF zFS Files

Create a directory where ZMF can create and manage zFS directories and files. This is not necessarily the directory where baseline, promotion, and production libraries reside, but staging libraries should be created in this directory.

- 1 Create a top-level directory for USS files that will be managed by ChangeMan ZMF instances that are owned by user-id SERUSER:

- a Create a top level directory:

```
/serdir
```

- b Change the owner and group owner of /serdir to SERUSER and SERGRP respectively, and propagate the change to all directories and files that may have been created under the top-level directory.

```
chown -R sert:cmntp /serdir
```

- c Set the permission bits for /serdir to allow SERUSER and ZMF Administrators in group SERGRP to READ, WRITE and EXECUTE, and allow all others to READ EXECUTE.

```
chmod 755 /serdir
```

- 2 Create and mount the zFS data set for /serdir:

- a Create the zFS data set for /serdir.

- b Mount the zFS data set at /serdir:

```
MOUNT FILESYSTEM('zFS datasetname') mountpoint('/serdir') TYPE(ZFS) MODE(RDWR)
AUTOMOV
```

- c Add the mount of /serdir to the BPXPRMnn member in the primary SYS1.PARMLIB to ensure that the mount for /serdir is executed at IPL.

Adjust Security on zFS Files Managed by ZMF

For any path entered into ZMF Administration for baseline, production, or promotion libraries, adjust the permissions to give the ZMF started task ownership with permission 755.



NOTES Exit exit program CMNEX093 makes it possible to override the ChangeMan ZMF default 755 permission for USS staging libraries. See the comments in the CMNEX093 program source delivered in the ASMSRC library.

Increase MAXPROCUSER or PROCUSERMAX

Unix System Services limits the number of simultaneous processes running under a userid (UID), even if the processes are initiated from multiple address spaces. ChangeMan ZMF can potentially create a large number of parallel processes inside USS as Java build jobs are file tailored and submitted under the ZMF UID.

The number of parallel processes per UID is limited by the MAXPROCUSER entry in BPXPRMxx. When this value is exceeded, USS fails the creation of new processes, which will cause jobs or tasks inside ZMF to fail. When creation of a process is failed, message BPXP005I is issued with a return code of 70 (unless suppressed by USS specifications).

A rough calculation for the number of processes required is:

```
2 * (# of parallel USS related jobs *executing* concurrently)
+ 2 * (# of concurrent ZMF users logged on)
```

If you do not want to increase the global limit using the MAXPROCUSER entry in BPXPRMxx, use the PROCUSERMAX parameter on the OMVS segment of the RACF profile for the ChangeMan ZMF userid.

```
ALTUSER userid OMVS(PROCUSERMAX(nnnn))
```

This command is described in "Unix System Services Planning", Section 3.

Enable CMNEX026 for LSH Listing

Listings from Java build processing are stored in zFS files in library type LSH. Library type LSH is coded in Java build skeletons, but it is not a reserved library type.

The following code is delivered in CMNEX026 to allocate an LSH staging library when language JAVA is processed.

```
*
* The following sample ensures that the zfs based listings libtype
* is allocated whenever a language name of JAVA is used
*
      CLC   X26$LANG,=CL8'JAVA'  java language?
      JNE   X26$0010             .no, skip java
      MVI   X26$WORK,C'Y'        indicate something added
      MVC   0(3,R2),=CL3'LSH'    alloc lsh for java
      LA    R2,3(,R2)            bump for next entry
```

Follow the instructions at the top of exit program CMNEX026 to enable the exit. There is no need for you to add Java library types to table X26@LTYP. You may also like to examine CMNEX032.

Configure ZMF Global and Application Administration

This section shows you entries in ChangeMan ZMF global and application administration that are required to manage Java components and work in zFS.

When you enter zFS paths and directories for staging and baseline files, those paths should be under the exclusive control of the user-id assigned to the SERNET / ZMF started task. Serena recommends that the path be under the high-level directory you defined in ["Create Top-Level Directory for ZMF zFS Files" on page 29](#).

The paths for production and promotion directories should also be under the exclusive control of the SERNET / ZMF started task, although your environment may require some sharing of write permission.

Global Staging Library Model zFS Name

When you check out a component that is stored in an zFS file, the staging library allocated for that component must be an zFS directory. On the **Global Parameters – Part 7 of 8**

panel (CMNGGP07), enter a Dev model zFS name to tell ChangeMan ZMF how to structure the staging path and directory name.

```

CMNGGP07                      Global Parameters - Part 7 of 8
Command ==> _____

Staging library model dataset names
Dev model dsname . . . CMNTP.S6.????.STG6.#####
Prd model dsname . . . CMNTP.S6.????.STG6.#####
Dev model zfs name . . /cmntp/s6/????/#####/d      +
Prd model zfs name . . /cmntp/s6/????/#####/p      +

"???" is placeholder for application name.
"#####" is placeholder for package number (.#000123).

zfs temp folder . . . /u/sert/C001/tmp/s6      +

Package master . . . CMNTP.S6.V810T06.CMNZMF.CMNPMAS
Cpnt mstr (short) . . CMNTP.S6.V810T06.CMNZMF.CMNCMPNT
Cpnt mstr (long) . . CMNTP.S6.V810T06.CMNZMF.CMNCMPNL
Delay file . . . CMNTP.S6.V810T06.CMNZMF.CMNDELAY
Ser#parm . . . CMNTP.SER810.C6.TCPIPORT
Impact analysis . . CMNTP.S6.V810T06.CMNZMF.IADSP

Email server . . . mail.serena.com      +
port . . . 00025

```



TIP You can use the same general naming pattern you use for PDS(E) libraries, substituting a slash for each period. However, the path should start with the high-level directory you defined in the Security for zFS section of this document.



NOTE ChangeMan ZMF does not use the information in the **Prd model zfs name** field on this panel. Instead, the **Prd staging model zfs** on the **site Site Information - Part 2 of 2** panel (where **site** is a variable value) is used.

Global zFS Temporary Folder

Some component processes in ZMF create temporary files. When you are working with a package component that is stored in an zFS file, temporary files will also be zFS files.

You specify a directory path for temporary zFS files on the **Global Parameters – Part 7 of 8** panel (CMNGGP07) shown above in field **zfs temp folder**. This field initially shows a top-level directory value of /tmp. Add at least one subdirectory to create a path where ZMF will create zFS temporary files.

```
zfs temp folder    ==> /tmp/s4
```

Global Site zFS Production Staging Model DSNAME

The **site Site Information – Part 2 of 2** panel (CMNGRST2) requires the **PRD staging model zFS** path for a remote site.

This example of the **site Site Information – Part 2 of 2** panel (CMNGRST2) shows the **Prd staging model zFS** path for a development site, where the path is the same as the **Dev model zFS name** on the **Global Parameters - Part 7 of 8** panel (CMNGGP07).

```
CMNGRST2          SERT6 Site Information - Part 2 of 2
Command ==>

ChangeMan ZMF subsystem id . . 6
Logical unit name . . . . . BUCKS +
JES node name . . . . . C001
Default unit name . . . . . SYSDA (Generic disk unit)
Default volume serial . . . .
ChangeMan ZMF delay file . . . CMNTP.S6.V810T06.CMNZMF.CMNDELAY
Ser#parm . . . . . CMNTP.SER810.C6.TCPIPORT
Prd staging model dsname . . . CMNTP.S6.????.STG6.#####
Prd staging model zFS . . . . /cmntp/s6/????/#####/d +
Transmission vehicle . . . . . IEBCOPY (IEBCOPY or Other)
Time difference . . . . . +0000 (+/- HHMM)
IP address or DNS name . . . . +
Port . . . . .

Site job statement information:
//CMNSTART JOB 'SERT6 SITE',
//          CLASS=A,MSGCLASS=X
//*
/* SITE SERT6 JOB STATEMENTS
```

This example shows the **Prd staging model zFS** path for a remote site, where the path is different from the **Dev model zFS name** on the **Global Parameters - Part 7 of 8** panel (CMNGGP07).

```
CMNGRST2          SERT6P1 Site Information - Part 2 of 2
Command ==>

ChangeMan ZMF subsystem id . . 7
Logical unit name . . . . . BUCKS +
JES node name . . . . . C001
Default unit name . . . . . SYSDA (Generic disk unit)
Default volume serial . . . .
ChangeMan ZMF delay file . . . CMNTP.S7.V810.CMNZMF.CMNDELAY
Ser#parm . . . . . CMNTP.SER810.C6.TCPIPORT
Prd staging model dsname . . . CMNTP.S7.????.STG7P1.#####
Prd staging model zFS . . . . /cmntp/s6/????/#####/p1 +
Transmission vehicle . . . . . IEBCOPY (IEBCOPY or Other)
Time difference . . . . . +0000 (+/- HHMM)
IP address or DNS name . . . . +
Port . . . . .

Site job statement information:
//CMNSTART JOB 'SERT6P1 SITE',
//          CLASS=A,MSGCLASS=X
//*
/* SITE SERT6P1 JOB STATEMENTS
```


Global and Application Library Types

Define like-source, like-load, and like-PDS library types for your Java components in global and application library types. This **application - Library Types Part 1 of 2** panel (CMNCLLT0) from a Java-only application shows the relationship between like-source and like-load Java library types.

CMNCLLT0		JZFS - Library Types Part 1 of 2				Row 1 to 11 of 11	
Command ==>						Scroll ==> <u>CSR</u>	
Lib	Order	Lke	Seq	Defer	Target	Sel	
type					type	Opt	
HTH <u>zFS resident HTML</u>	0	P		Y			
JAR <u>Java Archives</u>	0	L		Y			
JCF <u>Java Class files</u>	0	L		Y			
JCL <u>Execution JCL</u>	0	P		Y			
JCT <u>Java JAR Build Control</u>	0	S		Y	JAR		
JVL <u>zFS - JAVA executable class</u>	0	L		Y			
JVS <u>zFS - JAVA source type</u>	0	S		Y	JVL		
JVT <u>zFS - text type</u>	0	P		Y			
LSH <u>zFS Listings</u>	0	P		Y			
WAR <u>Java Web Archives</u>	0	L		Y			
WCT <u>Java WAR Build Control</u>	0	S		Y	WAR		
***** Bottom of data *****							



IMPORTANT! In some cases, library type definitions for Java components may not be intuitive because a component must be defined as like-source to initiate a build process, and the output of a build process must be defined as like-load so a source-to-load relationship can be recorded. How the library types in this example work in Java build processing is explained in [Chapter 4, "Working With Java" on page 39](#).

The global and application **Library Types Part 2 of 2** panels (CMNCLLT1) generally look like this with only **Data Set Type** specified in **Staging Dataset Attributes**.

CMNCLLT1		JZFS - Library Types Part 2 of 2	
Command ==>			
Library type: HTH - zFS resident HTML			
Like value: P		Defer value: Y	
Staging dataset attributes:			
Generic unit name	_____	(Generic group name or unit)	
Volume serial	_____	(Required if generic unspecified)	
Space units	_____	(trk, cyl or blk)	
Primary quantity	_____	(In above units)	
Secondary quantity	_____	(In above units)	
Directory blocks	_____		
Record format	_____		
Record length	_____		
Block size	_____		
Data set type	<u>ZFS</u>	(library, pds, zfs or blank)	
Extended attributes	_____	(no, opt or blank)	
Save staging versions	<u>ALWAYS</u>	(always/none/prompt)	
Enter "/" to select option:			
_ Checkout component description			
_ Checkout component activity file		Library type	



NOTE Staging Versions may be enabled for any text component, which includes zFS library types HTH, JCT, JAV, and WCT in the example provided here.

Global and Application Language and Compile Procedures

These are the only two language/procedure combinations required for Java.

CMNCLPRC		JZFS - Compile Procedures	Row 1 to 2 of 2
Command ==>			Scroll ==> CSR
Language	Procedure	Description	Order
JAVA	CMNJAR	Create Java archive	0
JAVA	CMNJAVA	Stage Java source	0
***** Bottom of data *****			

Define the JAVA language and the procedures shown here on the global and application **Language Names** and **Compile Procedures** panels.

Application Baseline Libraries

On the **application - Baseline Configuration Part 1 of 2** panel (CMNCBAS1), specify a **Baseline Storage Means** of **H** for all Java baseline repositories. Prior versions of baselined Java components are full copies, not delta decks.

CMNCBAS1		JZFS - Baseline Configuration Part 1 of 2	Row 1 to 10 of 10
Command ==>			Scroll ==> CSR
Type	Levels	Install in prod	Baseline storage means
HTH	3	N	H
JAR	3	Y	H
JCF	3	N	H
JCT	3	N	H
JVL	2	N	H
JVS	2	N	H
JVT	2	N	H
LSH	3	Y	H
WAR	3	Y	H
WCT	3	N	H
***** Bottom of data *****			

In the example shown here, only executable library types JAR and WAR are installed in production execution libraries (directories), along with build listings in library type LSH to provide a diagnostic reference in case of a production problem.

On the **application - Baseline Configuration Part 1 of 2** panel (CMNCBAS1), type line command **S** by a library type to display the **application - Baseline Configuration Part**

2 of 2 panel (CMNCBAS2) where you allocate new baseline paths and directories or verify existing directories.

```

CMNCBAS2      JZFS - Baseline Configuration Part 2 of 2      Row 1 to 2 of 2
Command ==> _____ Scroll ==> CSR

Library type:      JVS
Levels maintained:  2
Storage means:     zFS

Lvl Dataset name   +                                     Status
- -000 /cmntp/s6/jzfs/base/jvs/lvl-0
- -001 /cmntp/s6/jzfs/base/jvs/lvl-1
***** Bottom of data *****

```



CAUTION! JAR and WAR build processing uses path names to collect files to be included. Exercise care when defining directory paths for baseline and promotion libraries. The following naming structure is common for MVS baseline libraries, but it would result in -1 and -2 level libraries being included in JAR or WAR builds.

```

-000 /cmntp/s4/v710/base/jzfs/jav
-001 /cmntp/s4/v710/base/jzfs/jav/lvl-1
-002 /cmntp/s4/v710/base/jzfs/jav/lvl-2

```

On the **application - Baseline Configuration Part 1 of 2** panel (CMNCBAS2), type line command **A** next to a path name to create the path.

```

CMNCBAS2      JZFS - Baseline Configuration Part 2 of 2      Row 1 to 2 of 2
Command ==> _____ Scroll ==> CSR

Library type:      JVS
Levels maintained:  2
Storage means:     zFS

Lvl Dataset name   +                                     Status
- -000 /cmntp/s6/jzfs/base/jvs/lvl-0      *Allocated
A -001 /cmntp/s6/jzfs/base/jvs/lcl-1
***** Bottom of data *****

```



NOTE When you allocate an zFS baseline path and directory from the **application - Baseline Configuration Part 2 of 2** panel, there is no additional panel for library attributes as there is for PDS(E) library allocations.

On the **application - Baseline Configuration Part 1 of 2** panel (CMNCBAS2), type line command **V** next to a path name to verify the path and display the **zFS Information** panel if the path exists.

```

CMNCBAS2      JZFS - Baseline Configuration Part 2 of 2      Row 1 to 2 of 2
Command ==> _____ Scroll ==> CSR

Library type:      JVS
Levels maintained:  2
Storage means:     zFS

Lvl Dataset name   +                                     Status
-000 /cmntp/s6/jzfs/base/jvs/lvl-0      *Verified
V -001 /cmntp/s6/jzfs/base/jvs/lcl-1
***** Bottom of data *****

```

```

CMNDAIH                      ZFS Information
Command ==> _____

Pathname . . . /cmntp/s6/jzfs/base/jvs/lvl-2          +

Permissions . 755
File size . . 00008192
File owner . . SERT
Group owner . CMNTP
Created . . . 2015-03-22 21:25:49
Modified . . . 2015-03-22 21:25:49
Accessed . . . 2015-03-22 21:25:49
Link count . . 00002

```

Application Production Libraries

On the **application - site Production Libraries** panel (CMNCPRDL), specify paths for zFS components that you want copied to production execution libraries at package installation.

```

CMNCPRDL                      JZFS - SERT6 Production Libraries      Row 5 to 7 of 7
Command ==> _____      Scroll ==> CSR

Type Production dataset name      +
Temporary dataset name            +
Backup dataset name                +
____ JVS  /cmntp/s6/jzfs/prod/jvs  _____
          /cmntp/s6/nullfile
          /cmntp/s6/jzfs/prod/jvs/backup
____ JVT  /cmntp/s6/jzfs/prod/jvt  _____
          /cmntp/s6/nullfile
          /cmntp/s6/jzfs/prod/jvt/backup
____ JVL  /cmntp/s6/jzfs/prod/jvl  _____
          /cmntp/s6/nullfile
          /cmntp/s6/jzfs/prod/jvl/backup
***** Bottom of data *****

```



IMPORTANT! zFS components cannot be included in a temporary package. The **Temporary Dataset Name** is just a placeholder to satisfy ISPF panel edits.

Application Promotion Libraries

On the **application/site – Promotion Libraries** panel (CMNLRPM3), specify paths for test libraries you want to populate from staging directories.

CMNLRPM3
JZFS/SERT6 - Promotion Libraries
Row 3 to 8 of 8

Command ==>
Scroll ==> CSR

Promotion name: S6P1UT
Level: 10

Syslib	Lib	exclude	Target libraries	
JVS	N		/cmntp/s6/jzfs/prom10/jvs	+ Shadow
			/cmntp/s6/jzfs/prom10/jvs	+ Library 1
				+ Library 2
				+ Library 3
JVT	N		/cmntp/s6/jzfs/prom10/jvt	+ Shadow
			/cmntp/s6/jzfs/prom10/jvt	+ Library 1
				+ Library 2
				+ Library 3
JVL	N		/cmntp/s6/jzfs/prom10/jvl	+ Shadow
			/cmntp/s6/jzfs/prom10/jvl	+ Library 1
				+ Library 2
				+ Library 3
...				

Deploy Java Applications To WebSphere

ChangeMan ZMF can build a Java Web Application (EAR file) and deploy it to WebSphere on a z/OS system. Deployment means that the application is delivered to a location accessible to WebSphere, and a post-processing task uses published WebSphere APIs to refresh the running application.

ISPF file tailoring of ZMF skeleton CMNJAR generates batch job JCL to create JAR/WAR/EAR files. Standard ZMF promotion, install, and backout skeletons deliver EAR files to a WebSphere accessible location (typically the webapps folder). Three skeletons create JCL for post-processing of delivered EAR files:

- CMN\$\$WSP imbedded in promotion skeleton CMN\$\$PRO
- CMN\$\$WSI imbedded in install skeleton CMN20
- CMN\$\$WSB imbedded in backout skeleton CMN50

CMN\$\$WSP, CMN\$\$WSI and CMN\$\$WSB call WebSphere scripting APIs to refresh the application being updated. These skeletons must be customized for each environment to set variables for each application/libtype. The following table lists the variables that must be customized in each of these skeletons. Most of these values can be obtained from your WebSphere Application Server administrator.

Variable	Description
WSHOST	WebSphere HOST System - The host where WebSphere is located
WSPORT	WebSphere SOAP port - The WebSphere SOAP port
WSUSER	WebSphere Administrative ID
WSPASS	WebSphere Administrative id password

Variable	Description
WSSERVER	WebSphere Server - The WebSphere server name where the application is located
WSNODE	WebSphere Node - The WebSphere Node name where the application is located
WSAPPL	WebSphere Application - The WebSphere application name
WSSCRIPT	Jython Script file to execute - The script file to execute. The default is zmfws.jy. The path to this file also must be updated.

Also, the following details must be configured in each skeleton:

- Configure path to wsadmin - The path to the WebSphere wsadmin tool.
- Add component in CMN\$\$WSI - Component names must be added for the install skeleton.

Chapter 4

Working With Java

Packages containing Java components in zFS files must follow the standard ChangeMan ZMF package life cycle. However, some of the processes in that life cycle are different for Java components.

Java Build Processing	40
Impact Analysis for Java	44
Package Audit for Java	44
ERO Audit for Java	47

Java Build Processing

ChangeMan ZMF build processing requires a like-source library type for input and a like-load library type for output. When you are working with Java applications in ZMF, the like-source component may not actually be program source code, and the like-load output is an executable that is not a load module.

All files, including build listings, are zFS files.

Compile Java Source

This build process transforms Java source into a class file.

Components

Input / Output	Description	Like-Type	Extension	Library Type Example
Input	Java source	S	.java	JAV
Output	Java class file	L	.class	JCF
Output	zFS build listing	P	.list	LSH

Process

- Language: JAVA
- Procedure: CMNJAVA

Stage and recompile panels allow mixed case data in the COMPILE PARMS field when the LANGUAGE field is JAVA. Skeletons pass COMPILE PARMS options to the javac compiler, and COMPILE PARMS options are stored in component history for use in subsequent builds for the component.



CAUTION! The ChangeMan ZMF Java build process requires option -verbose, which is hard coded in build skeletons (delivered CMN\$\$JVA). If this option is nullified by an entry in the COMPILER OPTION field, the component build will fail.

Build Java Archive

This build process follows instructions in a file of JAR control statements to create a JAR file.

Components

Input / Output	Description	Like-Type	Extension	Library Type Example
Input	JAR control statements	S		JCT
Output	Java archive (JAR)	L	.jar	JAR
Output	zFS build listing	P	.list	LSH

Process

- Language: JAVA
- Procedure: CMNJAR

JAR Control Statements

This table describes JAR control statements.

Keyword	Description
*	<p>Comment</p> <p>Syntax: * in position 1</p> <p>Comment records are read and printed in the CMNPRINT data set, but content is ignored by JAR build processing.</p>
jarname	<p>Specifies the file name of the output JAR file that is written to the package staging library for the target JAR library type.</p> <p>Syntax: jarname=<i>filename</i></p> <p><i>filename</i> The output JAR name with extension. The JAR name may include a fragment of a path name.</p> <p>The <i>filename</i> string cannot exceed the maximum for the file system in use (255 characters in the current file systems).</p>
jarpath	<p>Specifies a ZMF library type to be included in the JAR file. Files are copied from application baseline libraries and package staging libraries for the library type. Files in subdirectories are copied.</p> <p>Syntax: jarpath=<i>libtyp,qualifier</i></p> <p><i>libtype</i> Three character library type. (Required, upper case.)</p> <p><i>qualifier</i> Fragment of a path name that acts as a filter to limit the scope of the copy to a subset of the files in the library type. (Optional, case sensitive.)</p>

Keyword	Description
jardir	<p>Specifies a ZMF library type to be included in the JAR file. Files are copied from application baseline libraries and package staging libraries for the library type. Files in subdirectories are NOT copied.</p> <p>Syntax: <code>jardir =libtyp,qualifier</code> (Note the space before =.)</p> <p><i>libtype</i> Three character library type. (Required, upper case.)</p> <p><i>qualifier</i> Fragment of a path name that acts as a filter to limit the scope of the copy to a subset of the files in the library type. (Optional, case sensitive.)</p>
jarfile	<p>Specifies a ZMF library type and the name of a file to be included in the JAR file. The file is copied from application baseline libraries and package staging libraries for the library type.</p> <p>Syntax: <code>jarfile=libtype,filename</code></p> <p><i>libtype</i> Three character library type. (Required, upper case.)</p> <p><i>filename</i> File name with extension, including full path name after baseline or staging library name. (Required, case sensitive.)</p> <p>If <i>filename</i> is omitted, no file is copied and no error is reported.</p>

JAR Control Examples

In the examples that follow, these are the contents of application baseline and package staging libraries for library type HTH.

Baseline library: /hthbaseline/

```
/hthbaseline/dir_1/adapter/file_x.html
/hthbaseline/dir_1/adapter/dir_2/file_x.html
/hthbaseline/dir_1/filter/file_x.html
/hthbaseline/dir_1/input/file_x.html
```

Staging library: /stagingmodel/HTH

```
/stagingmodel/HTH/dir_1/adapter/file_x.html
/stagingmodel/HTH/dir_1/adapter/dir_2/file_x.html
```

Example 1:

jarpath=HTH

Included files:

```
/stagingmodel/HTH/dir_1/adapter/file_x.html
/stagingmodel/HTH/dir_1/adapter/dir_2/file_x.html
/hthbaseline/dir_1/filter/file_x.html
/hthbaseline/dir_1/input/file_x.html
```

Example 2:

```
jarpath=HTH,dir_1/adapter
```

Included files:

```
/stagingmodel/HTH/dir_1/adapter/file_x.html
/stagingmodel/HTH/dir_1/adapter/dir_2/file_x.html
```

Example 3:

```
jardir =HTH
```

Included files:

```
/hthbaseline/dir_1/adapter/file_x.html
/hthbaseline/dir_1/adapter/dir_2/file_x.html
/hthbaseline/dir_1/filter/file_x.html
/hthbaseline/dir_1/input/file_x.html
```

Example 4:

```
jardir =HTH,dir_1/adapter
```

Included files:

```
/stagingmodel/HTH/dir_1/adapter/file_x.html
```



NOTE When a qualifier is specified for keyword `jardir`, files in subdirectories are excluded.

Build Web Archive

This build process follows instructions in a file of WAR control statements to create a WAR file.

Components

Input / Output	Description	Like-Type	Extension	Library Type Example
Input	WAR control statements	S		WCT
Output	Java Web archive (WAR)	L	.war	WAR
Output	zFS build listing	P	.list	LSH

Process

- Language: JAVA
- Procedure: CMNJAR

WAR Control Statements

The control statements used to build a WAR file are the same as those used to build a JAR file. See ["JAR Control Statements" on page 41](#).

Impact Analysis for Java

The only Impact Analysis relationships recorded for Java are for components included in JAR files, like static subroutines in composite executables.

Use the SUBROUTINE relationship on the **Impact Analysis Of Subordinate Components** panel and the **Component Bill Of Materials** panel.

Package Audit for Java

Package audit detects source-to-load inconsistencies and out-of-date issues in Java components like it does for non-Java components. There is no source-to-copy relationship in Java, and the only subroutine-to-composite relationship is between a Java archive (JAR) and its elements. Unlike MVS subroutines in composite loads, JAR elements may be any like-type.

Long names for Java components require a different package audit report format than is used for non-Java components. However, the conditions checked are similar to the conditions checked for PDS components, and the report contents are similar.

Package Out-of-Sync Conditions for Java

The following table lists the out-of-sync conditions that are analyzed for Java components. For more information, see Chapter 11 "Auditing a Package" in the *ChangeMan ZMF User's Guide*.

Out-of-Sync Condition	Description	RC
SYNCH0!	Package Master contains no record of this component.	0
SYNCH1!	Audit is unable to extract component statistics from the file system to perform one or more of the other SYNCH checks.	0
SYNCH2!	Like-source component was compiled without using the designated compile procedure and options.	12
SYNCH6!	Component in a staging library has no corresponding Component Activity File member in the package.	12
SYNCH7!	Element in a Java archive in a staging library was changed more recently than the Java archive in a staging library in the same package.	12
SYNCH8!	Element in a Java archive in a staging library was changed more recently than the Java archive in the baseline library.	8
SYNCH9!	Like-load component in a staging library does not match the corresponding like-source component in the package.	12
SYNCH10!	Component in the baseline library has changed since the component was checked out to a package staging library.	12
SYNCH11!	Component in a staging library was changed without using ChangeMan ZMF.	12
SYNCH12!	Component was copied into a staging library without using ChangeMan ZMF, or it is left over from a stage job that abended.	12

Out-of-Sync Condition	Description	RC
SYNCH14!	Package component is not in Active status.	12
SYNCH19!	A package master record points to a package component that is not in the staging library.	12
SYNCH20!	Element in a Java archive in a staging library has a SETSSI that does not match the SETSSI of the version of the element that audit expects would be obtained by the Java archive build from your package staging libraries (or eligible participating package) or from baselines (first found location).	8

Package Audit Report for Java Components

The package audit report for Java components has divisions similar to the package audit report for MVS components:

- Stand alone errors reported against package contents
- Relationship errors between header files and source
- Relationship errors between subroutines and composite executables
- Relationship errors between archives and included components

Each division is divided into sections relating to a common BUN. Heading information is similar to that provided in the non-zFS audit report.

The sample package audit report below validates package ACTP000062 that contains the following components.

CMNSTG01		STAGE: ACTP000062 Components				Row 1 to 4 of 4	
Command ==>						Scroll ==> CSR	
Name	+ Type	Status	Changed		Procname	User	Request
java040.java	JVS	ACTIVE	20150324 190145		CMNJAVA	USER015	
java050.java	JVS	ACTIVE	20150324 190230		CMNJAVA	USER015	
java060.java	JVS	ACTIVE	20150324 190306		CMNJAVA	USER015	
java070.java	JVS	ACTIVE	20150324 190345		CMNJAVA	USER015	
***** Bottom of data *****							

This is how each component was processed to produce the out-of-sync conditions shown in the sample audit report:

Component	Processing
java40.java	Checkout, edit, and stage.
java50.java	Checkout and stage without changes.
java60.java	Checkout, stage without changes, then baseline from another package.
java70.java	Stage from development.

This is the audit report for the package.

ChangeMan(R) ZMF (8.1.0 - 20141010) Audit TUESDAY MARCH 24, 2015 (2015/083) 20:44:26 Page 1

```
*****
*Simple Change Package      ==> ACTP000062 Created 2015/03/24 at 18:53:15 by USER015      *
*Package Installation Date ==> 2015/06/30      Package Status: DEV                      *
*Component Analysis Type   ==> zFS component list including non-relational errors.      *
*Library Appl:Libtype      ==> ACTP:LSH ACTR:LSH                                     *
*****
```

Component Name	Error	From	Timestamp	Package	User
java040.JVS.list		Stage Base	2015/03/24 19:01:47	ACTP000062 ACTP000061	USER015 USER015
java050.JVS.list		Stage Base	2015/03/24 19:02:32	ACTP000062 ACTP000061	USER015 USER015
java060.JVS.list		Stage Base	2015/03/24 19:03:07	ACTP000062 ACTP000063	USER015 USER015
java070.JVS.list		Stage Base	2015/03/24 19:03:47	ACTP000062 ACTP000061	USER015 USER015

ChangeMan(R) ZMF (8.1.0 - 20141010) Audit TUESDAY MARCH 24, 2015 (2015/083) 20:44:26 Page 2

```
*****
*Simple Change Package      ==> ACTP000062 Created 2015/03/24 at 18:53:15 by USER015      *
*Package Installation Date ==> 2015/06/30      Package Status: DEV                      *
*Component Analysis Type   ==> zFS component list including non-relational errors.      *
*Library Appl:Libtype      ==> ACTP:JVL ACTR:JVL                                     *
*****
```

Component Name	Error	From	Timestamp	Package	User
java040.class		Stage Base	2015/03/24 19:01:44	ACTP000062 ACTP000061	USER015 USER015
java050.class		Stage Base	2015/03/24 19:02:29	ACTP000062 ACTP000061	USER015 USER015
java060.class		Stage Base	2015/03/24 19:03:04	ACTP000062 ACTP000063	USER015 USER015
java070.class		Stage Base	2015/03/24 19:03:44	ACTP000062 ACTP000061	USER015 USER015

ChangeMan(R) ZMF (8.1.0 - 20141010) Audit TUESDAY MARCH 24, 2015 (2015/083) 20:44:26 Page 3

```
*****
*Simple Change Package      ==> ACTP000062 Created 2015/03/24 at 18:53:15 by USER015      *
*Package Installation Date ==> 2015/06/30      Package Status: DEV                      *
*Component Analysis Type   ==> zFS component list including non-relational errors.      *
*Library Appl:Libtype      ==> ACTP:JVS ACTR:JVS                                     *
*****
```

Component Name	Error	From	Timestamp	Package	User
java040.java		Stage Base	2015/03/24 19:00:15 2015/03/24 18:07:24	ACTP000062 ACTP000061	USER015 USER015
java050.java	DUPLIC!	Stage Base	2015/03/24 18:58:11 2015/03/24 18:07:24	ACTP000062 ACTP000061	USER015 USER015
java060.java	SYNCH10!	Stage Base	2015/03/24 18:58:15 2015/03/24 20:43:06	ACTP000062 ACTP000063	USER015 USER015
java070.java		Stage Base	2015/03/24 19:02:25 2015/03/24 18:07:24	ACTP000062 ACTP000061	USER015 USER015

ChangeMan(R) ZMF (8.1.0 - 20141010) Audit TUESDAY MARCH 24, 2015 (2015/083) 20:44:26

Page 4

Legend and Summary Report

The local level of audit chosen at this point; 4

4 - Audit is required and the return code must not exceed 4 which implies that there are no "out-of-synch" situations within the staging libraries nor the baseline libraries but at least one module of a staging library is a "duplicate" of its baseline counterpart

Out-of-synch messages (hint - search for "!" marks)

DUPLIC!	(Staging duplicates baseline)	====> 1
SYNCH0!	(Not in scope of audit or unknown)	====> 0
SYNCH1!	(Cmpnt statistics not available)	====> 0
SYNCH2!	(Compile/designated proc differ)	====> 0
SYNCH3!	(Unparsable load module)	====> 0
SYNCH4!	(cpy/hdr staging problem)	====> 0
SYNCH5!	(cpy/hdr baseline problem)	====> 0
SYNCH6!	(Activity file not checked out)	====> 0
SYNCH7!	(Static subcomponent stage problem)	====> 0
SYNCH8!	(Static subcomponent base problem)	====> 0
SYNCH9!	(Source and load discrepancy)	====> 0
SYNCH10!	(Version regression problem)	====> 1
SYNCH11!	(Component hash discrepancy)	====> 0
SYNCH12!	(Orphan module in staging)	====> 0
SYNCH13!	(Baseline/staging discrepancy)	====> 0
SYNCH14!	(Components not in active status)	====> 0
SYNCH15!	(Source to relationship problem)	====> 0
SYNCH16!	(CPY low-date problem in baseline)	====> 0
SYNCH17!	(CPY deleted problem in staging)	====> 0
SYNCH18!	(LOD deleted problem in staging)	====> 0
SYNCH19!	(Missing module in staging)	====> 0
SYNCH20!	(Inconsistent subroutine)	====> 0
SYNCH21!	(Scr/rename pkg component)	====> 0
SYNCH22!	(Scratch subcmpnt is in use)	====> 0
SYNCH23!	(Rename subcmpnt is in use)	====> 0

Highest return code encountered =====> 12

CMN3060A - This package has failed the audit.

CMN2696I - PACKAGE ACTP000062 FAILED THE AUDIT WITH A RETURN CODE OF 12.

Recommendation Summary Report

Listed below are some solutions to resolving out of synch situations that can be flagged within this audit report.

DUPLIC! (Staging duplicates baseline)
Delete component from staging or change contents of staging component.
For package in BAS status, indicates no changes in baseline since pkg installed - no action required.

SYNCH10! (Version regression problem)
Copy staging member to development library.
Checkout member again from the baseline library.
Resolve version regression.
Stage member.

CMN7540I - End of job; RC = 12

***** BOTTOM OF DATA *****

ERO Audit for Java

Like package audit, ERO release audit detects source-to-load inconsistencies and out-of-date issues in Java components like it does for non-Java components. There is no source-to-copybook relationship in Java, and the only subroutine-to-composite relationship is between a Java archive (JAR) and its elements. Unlike MVS subroutines in composite loads, JAR elements may be any like-type.

ERO audit analyzes components across release areas and prior releases.

Release Audit Error Numbers for Java

These ERO audit error codes are applicable to JAR components and can be detected by the current ERO release audit.

Error Numbers	Description
100	Identical components
312	Eligible baseline archive element not used by archive
315	Baseline archive element has a more recent date than archive
318	Archive element has a more recent date than archive in baseline
332	Baseline source is later than archive
382	Archive element is not included by baseline archive
401	Archive element has more recent date than archive
404	Source has a more recent date than archive
411	Designated compile procedure not used
413	Archive element deleted
416	Activity file not checked out
417	Version regression
421	Archive element not included in composite archive

For more information, see topic "Release Audit Error Numbers" Chapter 10 "Auditing Release Areas" in the *ChangeMan ZMF ERO Getting Started Guide*.

Known Exception in JAR Relationships

Build procedure CMNJAR includes SYSLIB-type processing to make Java components available for inclusion in a JAR file. However, JAR elements drawn from dependent release areas are not currently being registered in package master subroutine-to-composite relationship records.

Therefore, these audit errors are applicable to JAR components but are not currently detected for and JAR files and JAR elements in dependent release areas.

Error Numbers	Description
310	Eligible dependent area archive element not used by archive
311	Eligible prior release archive element not used by archive
313	Dependent area archive element has a more recent date than archive
314	Prior release archive element has a more recent date than archive
316	Archive element has a more recent date than archive in dependent area
317	Archive element has a more recent date than archive in prior rls
330	Dependent area source is later than archive
331	Prior release source is later than executable
380	Archive element is not included by dependent area archive
381	Archive element is not included by prior release archive

ERO Audit Report for Java Components

This section shows an example of an ERO audit report displaying Java components and relationships.

- Long component names extend across the page, on two lines if necessary.
- Component statistics are shown below the long name line(s).
- JAR files (composite components) are identified by >> in the left margin.
- JAR elements (with no >>) are listed below the JAR name and statistics.

Change Man Release Audit Report		Wednesday May		04,2011	(2011/124) 09:53:49		PAGE: 13	
***** (Release Area Processing - zFS Components)*****								
*Release Identifier		==> SDZFS001		Created: 20100528		Release Install Date ==> 20100528		*
*Area Identifier		==> UNIT		Area Status		==> UNBLOCKED		*
*Subcomponent relationships to libtype-(JAR)								

----- Previous Version -----				*----- Area Library -----*				

>>Component Name -> Subordinate Name								
Timestamp		Size	Area	Release	Libtype	Appl/Pkg#	Timestamp	Size
>>org/jdom/xpath/enh177473jarnew01.jar								
org/jdom/adapters/package.html		2010-03-30 07.22.00	193	ERR0312!	HTH			
org/jdom/adapters/AbstractDOMAdapter.class		2010-03-26 04.02.22	434	ERR0312!	JCF			
org/jdom/filter/package.html		2010-03-30 07.22.13	365	ERR0312!	HTH			
org/jdom/input/package.html		2010-03-30 07.22.23	432	ERR0312!	HTH			
org/jdom/output/package.html		2010-03-30 07.22.31	610	ERR0312!	HTH			
org/jdom/package.html		2010-03-30 07.22.41	524	ERR0312!	HTH			
org/jdom/transform/package.html		2010-03-30 07.22.49	282	ERR0312!	HTH			
org/jdom/xpath/enh177473hthnew01.hth				ERR0413!	HTH			
org/jdom/xpath/enh177473hth01.hth		2010-05-28 02.48.54	90	ERR0401!	HTH	STEV000138	2010-05-28 05.41.22	137
org/jdom/xpath/enh177473hth02.hth		2010-05-28 05.18.33	90	ERR0315!	HTH			
org/jdom/xpath/enh177473jcfnew01.class				ERR0413!	JCF			
org/jdom/xpath/enh177473jcf01.class		2010-05-26 01.36.50	423		JCF	STEV000138	2010-05-28 02.44.07	423
org/jdom/xpath/enh177473jcf02.class		2010-05-28 05.19.06	422	ERR0315!	JCF			
org/jdom/xpath/package.html		2010-03-30 07.22.58	170	ERR0312!	HTH			
org/jdom/xpath/HelloWorld1.class		2011-04-15 08.45.00	417	ERR0315!	JCF			
org/jdom/xpath/HelloWorld3.class		2010-04-28 07.21.21	417	ERR0312!	JCF			
>>org/jdom/xpath/enh177473jar01.jar								
2010-05-26 03.20.44		6619		JAR	STEV000138	2010-05-28 03.12.47	6659	
org/jdom/adapters/package.html		2010-03-30 07.22.00	193	ERR0312!	HTH			
org/jdom/adapters/AbstractDOMAdapter.class		2010-03-26 04.02.22	434	ERR0312!	JCF			
org/jdom/filter/package.html		2010-03-30 07.22.13	365	ERR0312!	HTH			
org/jdom/input/package.html		2010-03-30 07.22.23	432	ERR0312!	HTH			
org/jdom/output/package.html		2010-03-30 07.22.31	610	ERR0312!	HTH			

Appendix A

Technical Notes

This appendix provides additional technical information about working with Java and zFS in ChangeMan ZMF.

[CMNHUTIL - zFS File Utility](#)

52

CMNHUTIL - zFS File Utility

CMNHUTIL is a utility program for processing zFS files in batch. It was developed to overcome limitations on path names and file names in z/OS JCL and in dynamic allocation. CMNHUTIL performs these functions:

- Defines a new zFS file
- Copies a single zFS file
- Copies multiple zFS files
- Writes text to a zFS file
- Renames a zFS file
- Deletes a zFS file
- Delete a zFS directory

CMNHUTIL Input

- SYSIN records that specify zFS paths, directories, and files and the functions to be performed
- Input zFS paths, directories, and files specified in SYSIN records

Output

- Output zFS paths, directories, and files specified in SYSIN records
- SYSPRINT report of SYSIN input and processing results

Sample JCL

The following is a sample job fragment showing a CMNHUTIL step.

```
//WRJ2TMP EXEC PGM=CMNHUTIL, copy source files to work files
//          REGION=0M
//SYSPRINT DD DISP=(,PASS),DSN=&&LIST23,
//          UNIT=SYSDA,SPACE=(133,(1000,1000),RLSE)
//SYSIN DD DATA,DLM='++'
CREATEDIRECTORIES=Y
FILEPERMISSIONS=777
FILE=/u/ser/C001/tmp/s6/D63f1QV0loG/cmnJVS/jhfjav40.java
define
CREATEDIRECTORIES=Y
FILEPERMISSIONS=777
FILE=/u/ser/C001/tmp/s6/D63f1QV0loG/cmngen/jhfjav40.class
DEFINE
CREATEDIRECTORIES=Y
FILEPERMISSIONS=777
FILE=/u/ser/C001/tmp/s6/D63f1QV0loG/cmnlst/jhfjav40.list
DEFINE
CREATEDIRECTORIES=Y
FILEPERMISSIONS=777
FILEIN=/cmntp/s6/base/ACTP/stgedev/#000050/JVS/jhfjav40.java
FILEOUT=/u/ser/C001/tmp/s6/D63f1QV0loG/cmnJVS/jhfjav40.java
COPY
++
```

DD Statements

This table describes DD statements for CMNHUTIL.

DDNAME	I/O	Purpose
SYSIN	Input	Records that specify zFS paths, directories, and files and the functions to be performed IMPORTANT! Code an explicit delimiter ++ for SYSIN in-line data. /* is acceptable in zFS path names, and it will cause truncation if the default in-line data delimiter /* is assumed. //SYSIN DD DATA,DLM='++' . . . ++
SYSPRINT	Output	Report of SYSIN input and processing results
CMNSDFIL	Output	sidefile records for JAR ILIC use

PARM Options

There are no execution parameters input to utility program CMNHUTIL with a PARM= parameter in the EXEC statement.

SYSIN Parameters

SYSIN records specify zFS paths, directories, and files and the functions to be performed.

There are two types of SYSIN records:

- Keywords - SYSIN keyword statements specify input and output zFS paths, directories, and files. Keyword records also provide parameters and additional information for the function to be performed.
- Verbs - Verb records specify what action is to be taken on the zFS paths, directories, and files specified in SYSIN keyword records.

CMNHUTIL SYSIN Keywords

Keyword statements consist of a keyword and a value. Example:

```
FILEPERMISSIONS=775
```

If a keyword is relevant to an operation and it is omitted, the default value for that keyword is assumed.

This table describes CMNHUTIL SYSIN keywords.

SYSIN Keyword	Description
COMPRESS	Specifies whether output file should be compressed Valid values: Y/N Default: N
CREATEDIRECTORYS	Specifies whether new directory structures should be created Valid values: Y/N Default: N
DIRIN	Specifies input directory Valid values: A valid zFS path name Default: None
DIROUT	Specifies output directory Valid values: A valid zFS path name Default: None
FILE	Specify file for single file operations Valid values: A valid zFS file name Default: None
FILEAPP	Specify single output file for append operations Valid values: A valid zFS file name Default: None
FILEIN	Specify a single input file Valid values: A valid zFS file name Default: None
FILEOUT	Specify a single output file Valid values: A valid zFS file name Default: None
FILEPERMISSIONS	Specifies file permissions for output files Valid values: Valid Unix file permission string Default: 755
INPUTCOMPRESSED	Specifies whether input data file is compressed Valid values: Y/N Default: N

SYSIN Keyword	Description
PRESERVEMODDATE	Specifies whether file modification date should be preserved on copy operations Valid values: Y/N Default: N
REPLACE	Specifies whether files should be replaced in copy operations Valid values: Y/N Default: Y
SIDFILE	Writes sidefile records to CMNSDFIL Valid values: Y/N Default: N
SUBDIRS	Specifies whether subdirectories should be processed Valid values: Y/N Default: N
TEXTIN	Identifies text for SETTEXT operation Valid values: Any text Default: None

SYSIN Verbs

This table describes CMNHUTIL SYSIN verbs.

SYSIN Verb	Description
COPY	Copy a single file
COPYALL	Copy multiple files
DEFINE	Define a new file
DELETEFILE	Delete a file
RENAMEFILE	Rename a file
RMDIR	Delete a directory
SETTEXT	Write text to file

Valid SYSIN Keyword and Verb Combinations

Not every keyword is relevant to every verb. This table shows valid combinations of keywords and verbs.

	COPY	DEFINE	DELETEFILE	RENAMEFILE	SETTEXT	COPYALL	RMDIR
FILE		X	X				
FILEIN	X			X			
FILEOUT	X			X	X		
FILEAPP	X				X		
DIRIN						X	X
DIROUT						X	
FILEPERMISSIONS	X	X			X	X	

	COPY	DEFINE	DELETEFILE	RENAMEFILE	SETTEXT	COPYALL	RMDIR
CREATEDIRECTORYS	X	X			X	X	
SIDFILE	X					X	
TEXTIN					X		
SUBDIRS						X	X
COMPRESS	X					X	
INPUTCOMPRESSED	X					X	
PRESERVEMODDATE	X					X	
REPLACE	X					X	

SYSIN Record Syntax Rules

Follow these rules when coding SYSIN keyword statement and verb records.

- A CMNHUTIL operation is defined by one or more keyword statements followed by a verb.
- Each keyword statement or verb is coded on a separate SYSIN record.
- Keyword statements longer than 79 characters are continued by placing a non-blank character in position 80 and continuing the statement in the next SYSIN record, starting in position 1.
- SYSIN may contain multiple keyword statement / verb sets. Operations are performed serially and are initiated as a verb is read.

Return Codes and Error Messages

Utility CMNHUTIL provides two return codes:

- Internal return code displayed in SYSPRINT for each operation (verb), in format

verb RC:nnn

where nnn is the decimal value a for Unix System Services errno.

Non-zero internal return codes in SYSPRINT are preceded by an error message that explains the condition.

For the definition of an errno, see "Return Codes (Errnos) Listed by Value" in the *z/OS UNIX System Services Messages and Codes*.

- External program return code that indicates the overall success or failure of the program. This is the RC and COND CODE listed in the job listing.

CMNHUTIL considers the internal USS errno in setting the external program return code, but a non-zero USS errno may not be fatal to the execution of CMNHUTIL.

This table describes external return codes for utility CMNHUTIL.

Return Code	Description
00	Successful execution
04	A non-zero internal return code that is not considered fatal to the CMNHUTIL function being executed, or other non-fatal CMNHUTIL conditions.
08	Invalid SYSIN verb or keyword, invalid verb / keyword combination; non-zero internal return code that is considered fatal to the CMNHUTIL function being executed.

Reporting

This is an example of the CMNHUTIL report printed at the SYSPRINT DD statement.

```
*****
* DDNAME: WRJ2TMP.SYSPRINT
*****
CMNHUTIL (8.1.0 20141010 14.25) Started...
Keyword processed: CREATEDIRECTORIES          Y
Keyword processed: FILEPERMISSIONS             777
Keyword processed: FILE                         /u/ser/C001/tmp/s6/D63f1QV0log/cmnJVS/jhfjav40.java
Mkdir:
Mkdir:
define RC: 0000
Keyword processed: CREATEDIRECTORIES          Y
Keyword processed: FILEPERMISSIONS             777
Keyword processed: FILE                         /u/ser/C001/tmp/s6/D63f1QV0log/cmnJVS/jhfjav40.class
Mkdir:
DEFINE RC: 0000
Keyword processed: CREATEDIRECTORIES          Y
Keyword processed: FILEPERMISSIONS             777
Keyword processed: FILE                         /u/ser/C001/tmp/s6/D63f1QV0log/cmnJVS/jhfjav40.list
Mkdir:
DEFINE RC: 0000
Keyword processed: CREATEDIRECTORIES          Y
Keyword processed: FILEPERMISSIONS             777
Keyword processed: FILEIN                      /cmntp/s6/base/ACTP/stgedev/#000050/JVS/jhfjav40.java
Keyword processed: FILEOUT                     /u/ser/C001/tmp/s6/D63f1QV0log/cmnJVS/jhfjav40.java
File: /cmntp/s6/base/ACTP/stgedev/#000050/JVS/jhfjav40.java copied to: /u/ser/C001/tmp/s6/D63f1QV0log/cmnJVS/jhfjav40.java
COPY RC: 0000
```

CMNHUTIL Examples:

- Copy a single file


```
//CMNHUTIL EXEC PGM=CMNHUTIL
//SYSPRINT DD SYSOUT=*
//SYSIN DD DATA,DLM='++'
FILEIN=/u/username/test.txt
FILEOUT=/u/username/backup.txt
COPY
++
```
- Copy an entire directory


```
//CMNHUTIL EXEC PGM=CMNHUTIL
//SYSPRINT DD SYSOUT=*
//SYSIN DD DATA,DLM='++'
DIRIN=/u/username/
DIROUT=/u/usernamebackup/
```

```
FILEPERMISSIONS=777  
CREATEDIRECTORIES=Y  
SUBDIRS=Y  
COPYALL  
++
```

Symbols

.class 40

.jar 41

.java 40

.list 40, 41, 43

.war 43

* 41

/tmp 31

A

administration, ZMF 30–38

Adobe Acrobat 7

audit, package Java

description 44–47

report 45

SYNCH conditions 44

audit, release Java

description 47–49

error codes 48

report 49

B

baseline libraries 34

BPX.SERVER 28

build

Java archive JAR 40

Java source 40

Java Web archive WAR 43

build control

JAR 41

WAR 43

C

case sensitive fields 20–23

data set type 21

mixed case 21

ChangeMan For Eclipse 12

ChangeMan ZMF Client Pack 12

class

FACILITY 28

UNIXPRIV 28

clearing, long fields 18

CMNCKI02 panel 20

CMNEX026 exit 30

CMNEX093 exit 29

CMNJAR, procedure 34

CMNJAVA, procedure 34, 40, 41, 43

command

LONG 18

- XLONG 18
- component name with directory 16, 23–25
- configure
 - administration, ZMF 30–38
 - baseline libraries 34
 - CMNEX026 30
 - language 34
 - library type 33
 - procedure 34
 - production libraries 36
 - promotion libraries 37
 - security 28, 29
 - staging model 30, 32
 - USS 28–30
- conventions, font 9
- D
- data set type, case sensitive fields 21
- directory
 - /tmp 31
 - top-level 29
- documentation
 - ZMF set 5
- E
- Eclipse 12
- ERO 20
- EXPAND (zoom) 17
- EXPAND panel field 23–25
- F
- FACILITY class 28
- file permission 29
- font, conventions 9
- H
- HFS
 - /tmp 31
 - baseline libraries 34
 - production libraries 36
 - storage means 34
 - support summary 12
 - top-level directory 29
- I
- IBM Rational Developer 12
- impact analysis 44
- J
- JAR
 - build 40
 - build control 41

- language 41
- procedure 41
- JAR build control
 - * 41
 - examples 42
 - jardir 42
 - jarfile 42
 - jarname 41
 - jarpath 41
- jardir, JAR build control 42
- jarfile, JAR build control 42
- jarname, JAR build control 41
- jarpath, JAR build control 41
- Java
 - .class 40
 - .jar 41
 - .java 40
 - .list 40, 41, 43
 - .war 43
 - audit, package 44–47
 - audit, release 47–49
 - build 40
 - impact analysis 44
 - language 40
 - procedure 40
 - support summary 12
- JAVA, language 34, 40, 41, 43
- L
- language, JAVA 34, 40, 41, 43
- library type
 - configure 33
 - LSH 30, 40, 41
- LONG command 18
- long fields 16–20
 - alternate panels 18
 - clearing 18
 - ERO 20
 - LONG command 18
 - right justified 20
 - scrolling 16
 - XLONG command 18
 - zoom (EXPAND) 17
- LSH library type 30, 40, 41
- M
- MAXPROCUSER 29
- MIXED CASE panel field 21–23

mixed case, case sensitive fields 21

O

OMVS segment 28

P

package audit 44–47

permission, file 29

PRD STAGING MODEL HFS field 32

procedure

 CMNJAR 34

 CMNJAVA 34

procedure, CMNJAVA 40, 41, 43

PROCUSERMAX 29

production libraries 36

promotion libraries 37

R

RDz 12

release audit 47–49

S

scrolling, long fields 16

security

 BPX.SERVER 28

 CMNEX093 29

 configure 28

 FACILITY class 28

 file permission 29

 OMVS segment 28

 SUPERUSER.FILESYS 28

 UID(0) 28

 UNIXPRIV class 28

STAGE NAME panel field 25

staging model 30, 32

storage means 34

SUPERUSER.FILESYS 28

SYNCH conditions, Java 44

T

tmp directory 31

top-level directory 29

U

UID(0) 28

USS, configure 28–30

W

WAR

 build 43

 build control 43

 language 43

 procedure 43

X

XLONG command 18

Z

ZMF documentation 5

zoom 17