



Hewlett Packard
Enterprise

Coordinator

Software Version: 11.5.0

Release Notes

Document Release Date: October 2017

Software Release Date: October 2017

Legal notices

Warranty

The only warranties for Hewlett Packard Enterprise Development LP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HPE shall not be liable for technical or editorial errors or omissions contained herein.

The information contained herein is subject to change without notice.

Restricted rights legend

Confidential computer software. Valid license from HPE required for possession, use or copying. Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

Copyright notice

© Copyright 2017 Hewlett Packard Enterprise Development LP

Trademark notices

Adobe™ is a trademark of Adobe Systems Incorporated.

Microsoft® and Windows® are U.S. registered trademarks of Microsoft Corporation.

UNIX® is a registered trademark of The Open Group.

This product includes an interface of the 'zlib' general purpose compression library, which is Copyright © 1995-2002 Jean-loup Gailly and Mark Adler.

Documentation updates

The title page of this document contains the following identifying information:

- Software Version number, which indicates the software version.
- Document Release Date, which changes each time the document is updated.
- Software Release Date, which indicates the release date of this version of the software.

To check for recent software updates, go to <https://downloads.autonomy.com/productDownloads.jsp>.

To verify that you are using the most recent edition of a document, go to [https://softwaresupport.hpe.com/group/softwaresupport/search-result?doctype=online help](https://softwaresupport.hpe.com/group/softwaresupport/search-result?doctype=online+help).

This site requires that you register for an HPE Passport and sign in. To register for an HPE Passport ID, go to <https://hpp12.passport.hpe.com/hppcf/login.do>.

You will also receive updated or new editions if you subscribe to the appropriate product support service. Contact your HPE sales representative for details.

Support

Visit the HPE Software Support Online web site at <https://softwaresupport.hpe.com>.

This web site provides contact information and details about the products, services, and support that HPE Software offers.

HPE Software online support provides customer self-solve capabilities. It provides a fast and efficient way to access interactive technical support tools needed to manage your business. As a valued support customer, you can benefit by using the support web site to:

- Search for knowledge documents of interest
- Submit and track support cases and enhancement requests
- Access product documentation
- Manage support contracts
- Look up HPE support contacts
- Review information about available services
- Enter into discussions with other software customers
- Research and register for software training

Most of the support areas require that you register as an HPE Passport user and sign in. Many also require a support contract.

To register for an HPE Passport ID, go to <https://hpp12.passport.hpe.com/hppcf/login.do>.

To find more information about access levels, go to <https://softwaresupport.hpe.com/web/softwaresupport/access-levels>.

To check for recent software updates, go to <https://downloads.autonomy.com/productDownloads.jsp>.

Contents

New in this Release 5

Resolved Issues 7

Notes 8

Documentation 9

New in this Release

This section lists the enhancements to HPE Coordinator version 11.5.0.

- You can now configure GSS authentication on the ACI and service ports without using ACI encryption. In this mode, all connections to the ports must be authenticated using GSSAPI and the Negotiate HTTP authentication mechanism.

To use GSS authentication, you must set the `GSSServiceName` parameter in the `[Server]` section to the full service name, domain, and Kerberos realm for the service. You can then set the `RequireGSSAuth` parameter in the `[Server]` section to enable GSS authentication on the ACI port, and set `RequireGSSAuth` in the `[Service]` section to enable GSS authentication on the service port.

NOTE:

You cannot configure `RequireGSSAuth` with the `[ACIEncryption]` configuration options. If you attempt to configure both, the server does not start.

This method provides an authentication requirement only. HPE recommends that you use it in conjunction with TLS/SSL to encrypt the authentication data.

- The `GSSServiceName` parameter has been added to the `AddController` action to allow you to set the service name for the child Controller components.

NOTE:

If you use GSSAPI authentication, you cannot use SSDP to automatically detect Controllers. You must manually add the Controllers by host and port.

- The `GetControllers` action now returns the GSSAPI service name of your Controllers, if you have configured GSSAPI authentication.

CAUTION:

Coordinator stores the service names in local storage files, and in a configured remote Controller SQL database. Storing the service names changes the SQL schema from earlier versions of Controller and Coordinator. Coordinator 11.5.0 automatically updates the schema when it starts. The updated tables are not compatible with earlier versions of Coordinator and Controller.

- The Coordinator Lua functions and methods have the following changes:
 - New functions and classes have been added for manipulating and parsing JSON. The new functions are `parse_json`, `parse_json_array`, and `parse_json_object`. The new classes are `LuaJsonArray`, `LuaJsonObject`, and `LuaJsonValue`.
 - New general Lua functions have been added for manipulating and parsing IDOL documents. The new functions are `parse_document_idx`, `parse_document_xml`, and `parse_document_csv`.
 - You can now call the `insertJson` method on `LuaField` objects as well as `LuaDocument` objects. You can also pass it one of the new `LuaJsonArray` or `LuaJsonObject` objects instead of a string.
 - The `LuaLogService` class and `get_log_service` function have been added. You can use these options to write log messages to a custom log file (instead of the standard ACI server log files).
 - The `get_config` function now uses the standard ACI server configuration file if you do not

specify the path argument.

- The general function `get_log(config, logstream)` has been deprecated. This function has been replaced with the new `get_log(log_type)` function.
- All ACI server ports now support the `Expect: 100-continue` HTTP header. Previously, third-party client applications that used this header (for example, using the `cURL` utility with the `-F` option to POST form data) could experience increased latency when communicating with the ACI server.

The following feature was released in Controller 11.4.1.

- Coordinator now supports running in OEM-licensed environments. Coordinator, Controller, and all registered services must use the same OEM license key.

NOTE:

To use OEM licensing with Coordinator and Controller, you must update both components to version 11.4.1 or later. If you are using these components with IDOL Site Admin, you must also update the IDOL Site Admin application to version 11.4.1 or later.

Resolved Issues

This section lists the resolved issues in Coordinator version 11.5.0.

- When an authorization role defined `Actions`, `ServiceActions`, or `IndexActions`, and the authorization role `Clients` parameter contained host names, calling the `ShowPermissions` action could result in an interruption of service.

Notes

These notes provide extra information about installing and using Coordinator.

- The SQL database schema has been updated. Coordinator 11.5.0 automatically updates the schema when it starts.

NOTE:

The updated tables are not compatible with earlier versions of Controller and Coordinator.

- The following configuration parameters for setting server action authorization by client IP address have been deprecated:
 - [Server] AdminClients
 - [Server] IndexClients
 - [Server] QueryClients or UserClients
 - [Service] ServiceControlClients
 - [Service] ServiceStatusClients

You can now use the [AuthorizationRoles] configuration section to set up authorization for your servers more flexibly. These configuration parameters are still available for existing implementations, but they might be incompatible with new functionality. The parameters might be deleted in future.

Documentation

The following documentation was updated for this release.

- *Coordinator Reference*